

## Glacier - C2S SBS/White Folding Carton

The industry-best solution for high-impact retail packaging. A two-ply laminated board that provides durability and exceptional visual appeal. Both plies are coated SBS, which provides superior print surface with white throughout.

### Features

### Benefits

Consistency	Best-in-class uniformity for exceptional runnability on converting and filling equipment, which results in maximized efficiency. Glacier also performs well in scoring, folding, foiling, embossing and die cutting techniques.
Superior Runnability	Compared to micro/mini flute corrugated, this laminated construction is significantly more “press friendly” when it comes to runnability, product output, and waste.
Smooth Surface	The C2S smooth surface offers outstanding ink holdout, sheet cleanliness and consistency in graphic or packaging application to deliver a visual aesthetic that denotes high quality.
Fade Resistance	Classic white styling is achieved without the need for Optical Brightening Agents (OBA), resulting in high whiteness without the risk of fading, commonly associated with some OBA grades.

### Popular Uses

Graphics	POP Displays Signage	
Packaging/Folding Carton	Beverages Consumer Electronics Cosmetics Luxury Merchandise Pharmaceutical	Refrigerated & Frozen Food Small Appliances & Hand Tools Sporting Goods Software & Peripherals Toys & Games

PROPERTY	TEST	Glacier C2S SBS/White		
CALIPER (pts)	T 411 om-97*	0.028	0.032	0.036
BASIS WEIGHT (lbs/msf)	T 410 om-98	121	126	136
RING CRUSH (MD)	7 818 om-97	290	300	310
RING CRUSH (CD)	T 818 om-97	240	250	260
STIFFNESS (MD)	T 489 om-99	980	1120	1340
STIFFNESS (CD)	T 489 om-99	510	580	615
SMOOTHNESS	T 538 om-01	20	20	60
BRIGHTNESS	T 452 om-98	86	86	86
GLOSS	T 480 om-99	55	55	55
MOISTURE (%)	T 412	6.7	7.1	7.5

\*Pre-laminated Calipers

352 Sixth Street  
Menasha, WI 54952

Phone 920.969.3600  
Toll Free 888.997.6543  
Fax 920.969.3688

[www.dura-fibre.com](http://www.dura-fibre.com)

Statement of Practical Use  
As with all materials, this product should be tested thoroughly under end user conditions to ensure it meets the requirements of the specific application.

Please see our Warranty online at [www.dura-fibre.com](http://www.dura-fibre.com)

DF008 0908